

PT- 19: 45/52 kW (EEx)EI. Centrifugal Pump Unit PT-19: 45/52 kW(EEx)EI.Sentrifugal Pumpeskid



Pump Pumpe	AZCUE (Alu Bronze) - Series AN 80 – 250 Serial no: 255432 Pmax: 6,5 bar, Qmax: 2625 l/min @ 50 Hz (2900 r/min) Pmax: 10,5 bar, Qmax: 3500 l/min @ 60 Hz (3500 r/min)
Motor	Brook Crompton -Typ : W-EF225MN-H Serial no : GX 033652 BAS.no : 98E117X IIB T4 400V (D), 45 kW, 2955 r/min, 77.5 A, 50 Hz 660-690V (Y), 45 kW, 2955 r/min, 46.6-44.5 A, 50 Hz 440-480V (D), 52 kW, 3540 r/min, 81.0-74.0 A, 60 Hz 660V (Y), 40 kW, 3550 r/min, 42,3 A, 60 Hz 690V (Y) 45 kW, 3545 r/min, 44,7 A, 60Hz
Start Cabinet Starteskap	HINECO - EEx de IIC T6 400 V – 440 V – 480 V – 660 V – 690 V – 50/60 Hz Serial no : 01-002 , Nemco no : 01 . 464 R
Connections Anslutninger	Pressure / Trykk: 4" Weco FIG 206 Female Half. Suction / Sug : 4" Weco FIG 206 Male Half.
Frame & Lifting Cert. Ramme & Løftesert.	PT-19-Frame. Acc.to D.N.V. 2.7.1 (Cert.no: 3 0031 / 2006) Slings ID(C0601607/1/15) Acc.to D.N.V. 2.7.1 (Cert.no: 1693/1 / 2006) Shackles ID(LCO/87) Acc.to D.N.V. 2.7.1 (Cert.no: 1693/1 / 2006)
Dimension (LxWxH) Dimensjoner (LxBxH)	2000 x 1100 x 2000 [mm]
Weight Vekt	ca. 2000 kg (Tara 3 000 kg)